

strong/strong adhesive



SPRINTIS Schenk GmbH & Co. KG Ludwig-Weis-Str. $11 \cdot$ D-97082 Würzburg Tel. +49 (0) 931 / 40 41 6-288 \cdot Fax: -100

www.sprintis.eu · info@sprintis.eu

12/2022

Applications & purposes

The marking tape unrolls smoothly and quietly and is best suited for marking and labeling in the office, workshop or warehouse. It is also used as a bag neck sealer tape for bundling, packaging and especially by means of our bag neck sealer for easy and quick sealing of bags (e.g. our flat bags) in manufacturing or converting companies, in warehouses or in the packaging area. So for the common bag neck sealers, this tape serves as a bag sealer replacement roll.

Characteristics

Adhesive type	nature rubber
Carrier material	PVC-Foil
Thickness (adhesive & carrier)	0,053 mm
Peel adhesion, adhesive strength (open side)	4,75N/25mm
Tensile strength	125N/25mm
Elongation at break	90%
Food contact	Not tested

Storage recommendation / Shelf life

Under normal storage conditions in a room climate (approx. 50% relative humidity & approx. $20\,^{\circ}$ C room temperature) the product in its original packaging has a storage period of at least 12 months after receipt by the customer.

Disclaimer

Our recommendations are based on our most current knowledge and experience. As our products are used in conditions beyond our control, we cannot assume any liability for damage caused through their use. Users of our products are solely responsible that the product is suitable for its intended application, and have determined such at their sole discretion. Users must comply with any applicable legislation and/or testing requirements for the finished article, and are responsible for bringing their products to market.

This publication does not constitute any warranty, express or implied, and is intended only for the recipient and cannot therefore be transferred to any third part. We cannot assume any liability for the use of our products in conjunction with other materials.